Specifications

Structure for Ranch

Engineered 2 x 4 trusses at 16 inch on center (Standard price includes up to 50 lb. load)

2 x 10 floor joists

4 foot rise or 4:12 pitch (see salesperson)

16 inch eave

30 year architectural shingles Prefinished aluminum fascia

3/4 inch tongue and groove plywood floor

2 x 6 exterior wall framing

2 x 6 and 2 x 4 interior walls

#2 or better lumber

R-50 insulation in ceiling (R-38 in vaulted ceilings) (R30 under floor, by owner)

R-21 or higher total wall insulation

Primed Hardie™ fiber cement siding, or maintenance-free Great Barrier™ vinyl siding and soffit

2 x 10 or LVL perimeter joists

Double top plate interior and exterior

Steel insulted exterior doors

Ply-GemTM vinyl double glazed windows with screens, low E, argon filled

Structure for 1½ Story

All of the above features with revisions as noted below:

No insulation on second floor

2 x 10 roof rafters

2 x 10 floor joists on first and second floor

10:12 roof pitch with reduced eave

Two six foot dormers on Cape Cod style

Interior

Full eight foot ceiling height
Tape and textured drywall
Ceiling lights in all rooms
Two TV and two phone jacks
Hollow core flush interior doors

Painted except touchup and marriage lines

Windows fully cased to match doors and

molding Doorbell

Vinyl floor covering and/or

Mohawk™ carpet

Seven pound carpet pad

Bathrooms

Two full bathrooms (in ranch models)

Gerber™ toilets Lasco™ tub/showers Single lever faucet

Swanstone™ single bowl vanity top Three door mirrored medicine cabinet

<u>Kitchen</u>

Laminate countertop with hundreds of choices

Oak countertop edge Single lever faucet

Double bowl stainless steel sink

Merillat™ Spring Valley Oak™ recessed-panel

cabinets Utility

PEX plumbing (copper optional) Washer/dryer connections 200 amp service panel

Meter base (if attached to home)

Two hose bibs

Exterior carriage lights by doors